

Versa Lift Installation Guide for Treadplate Platform Cover

INSTALLATION OPTION A: Install without bolts.

CAUTION: The inside edges of the tread plate cover are sharp! Wear gloves while handling the tread plate cover during installation.

Installation After the Lift has been Assembled:

1. Lower the platform to garage floor.
2. Carefully tip the tread plate cover into the platform frame (Fig. 1).
3. Gently lower the tread plate cover over the platform. The platform should fit completely inside the tread plate cover (Fig. 1).

If you have problems with this installation, call Byers Products for more assistance at 405-943-1468.

Origination Date 1-23-09. Copyright BPG All rights are reserved.

INSTALLATION OPTION B: Install using bolts.

CAUTION: The inside edges of the tread plate cover are sharp! Wear gloves while handling the tread plate cover during installation.

Installation During Lift Assembly:

1. Follow the Versa Lift Assembly Guide except on page 16, substitute Fig. 2 below for Fig. 26. Use the 4 2-1/4" bolts supplied with this tread plate cover instead of the 2" bolts normally used to assemble the platform.

Installation After the Lift has been Assembled:

1. Lower the platform to garage floor.
2. Remove the 8 screws that connect the door panel to the lifting platform as shown in Fig. 28, page 16 of the Versa Lift Assembly Guide.
3. Raise the platform a couple of feet above the floor, then remove the 1/4-20 x 2" screws at the 4 corners of the lifting platform.
4. Carefully tip-in the tread plate cover (Fig. 1).
5. Install the 2-1/4" long carriage bolts provided with this tread plate cover as shown in Fig. 2 below, then tighten the locknuts securely.
6. Lower the platform to the floor and re-connect the door panel. Follow instructions in the Assembly Guide.

